

MV-CA050-12UM/UC

5.0MP2/3"CMOSUSB3.0AreaScanCamera



GEN*i*CAM

US3TM
VISION


Introduction

MV-CA050-12UM/UC camera adopts Sony® IMX264 sensor to provide high-quality image. It uses USB3.0 interface to transmit non-compressed images in real time, and its max. frame rate can reach 47 fps (mono camera) or 60 fps (color camera) in full resolution.

Key Feature

- Supports auto and manual adjustment for gain, exposure control, white balance, etc.
- Supports hardware trigger, software trigger, free run, etc.
- Adopts M2 screw holes for securing cable that connects USB3.0 interface.
- Compatible with USB3 Vision Protocol, GenICam Standard, and the third-party software based on these protocol and standard.

Dimension



Available Model


□ Mono camera: MV-CA050-12UM

□ Color camera: MV-CA050-12UC

Applicable Industries

Electronic semiconductor, factory automation, liquor and beverage, medicine packing, etc.

Sensor Quantum Efficiency



Specification

Model	Camera	MV-CA050-12UM	MV-CA050-12UC
Sensor	type		
Sensor	model	CMOS, global shutter	
Pixel	size	Sony® IMX264	
Sensor	size	3.45 μm × 3.45 μm	
Resolution	Max.	2/3"	
frame	rate	2448 × 2048	
Dynamic	range	47 fps @2448 × 2048	60 fps @2448 × 2048
SNR	Gain	72 dB	
Exposure	time	40.2 dB	
		0 dB to 24 dB	0 dB to 20 dB
		UltraShort exposure mode: 1 μs to 14 μs	
		Standard exposure mode: 15 μs to 10 sec	
Exposure	mode	Off/Once/Continuous exposure mode	
Mono/color		Mono	Color
Pixel	format	Mono 8/10/10p/12/12p	Mono 8/10/12, Bayer RG 8/10/10p/12/12p, YUV422Packed, YUV422_YUYV_Packed, RGB 8, BGR 8
Binning		Supports 1 × 1, 2 × 2, 4 × 4	
Decimation		Supports 1 × 1, 2 × 2	
Reverse	image	Supports horizontal and vertical reverse image output	
Electrical feature			
Data	interface	USB3.0, compatible with USB2.0	
Digital	I/O	6-pin P7 connector provides power and I/O, including opto-isolated input × 1 (Line 0), opto-isolated output × 1(Line 1), and bi-directional non-isolated I/O × 1 (Line 2)	
Power	supply	9 VDC to 24 VDC, supports USB3.0 power supply	
Power	consumption	Typ. 2.9 W @5 VDC (USB3.0 provides power supply)	Typ. 3.3 W @5 VDC (USB3.0 provides power supply)
Mechanical			
Lens	mount	C-mount	
Dimension		29 mm × 29 mm × 30 mm (1.1" × 1.1" × 1.2")	
Weight		Approx. 80 g (0.18 lb.)	
Ingress	protection	IP30 (under correct lens installation and wiring)	
Temperature		Working temperature: 0 °C to 50 °C (32 °F to 122 °F) Storage temperature: -30 °C to 70 °C (-22 °F to 158 °F)	
Humidity		20% to 80% RH, non-condensing	
General			
Client	software	MVS or third-party software meeting with USB3 Vision Protocol	
Operating	system	32/64-bit Windows XP/7/10, 32/64-bit Linux and 64-bit MacOS	
Compatibility		USB3 Vision, GenICam	
Certifications		CE, RoHS, KC	

HIKROBOT

Hangzhou Hikrobot Co., Ltd.
en.hikrobotics.com



VISCON TECHNOLOGY CO., LTD.
54/88 KHLONGSEE, KHLONG LUANG DISTRICT, PATHUM THANI 12120 THAILAND
TEL : 02-0009297
MB : 0809293068
E-MAIL : SALE@VISCONTECHNOLOGY.COM

© Hangzhou Hikrobot Co., Ltd. All Rights Reserved.

Hangzhou Hikrobot does not tolerate any infringement. Any organization or individual may not imitate or reproduce in whole or in part of the content. The data herein is based on Hikrobot's internal evaluation. Actual data may vary depending on specific configuration and operating condition. The information herein is subject to change without notice. All the content has been checked conscientiously. Nevertheless, Hikrobot shall not be liable to damages resulting from errors, inconsistencies or omissions.