OPT® Machine Vision

VISCON

OPT CC1 Series Area Scan Cameras

OPT-CC1-C060-UR1-10

- USB3.0 interface, theoretical transmission bandwidth of 5Gbps, supports power supply via USB interface.
- Support ISP functions including Gamma, LUT, Black level, Brightness and Contrast etc.
- Support Hardware Trigger, Software Trigger, Free Run Mode.
- Built-in large-capacity frame cache, used for data transmission or image retransmission in burst mode.
- Support multiple image data formats output, ROI, Reverse and AutoFunction etc.
- Compatible with USB3 Vision Protocol and GenICam Standard, convenient for third-party connection.

Specification

Model	Sensor model	Sensor type	Shutter type	Resolution	Frame rate	Pixel size	Sensor size	Mono/Color
OPT-CC1-C060-UR1-10	IMX178	CMOS	Rolling	3072 × 2048	60.9 fps	2.4 µm×2.4 µm	1/1.8"	Color

Name	6 MP Color USB3.0 Area Scan Camera
Pixel format	Mono 8/10/10Packed/12/12Packed, BayerGB 8/10/10Packed/12/12Packed, YUV422Packed, YUV422 YUYV Packed
Max Frame rate	60.9 fps @ 3072 ×2048 BayerGB 8
Dynamic range	72 dB
SNR	41.3 dB
Gain	0 dB ~ 24 dB
Exposure time	8 µs ~ 3.86 s
Trigger mode	Software Trigger/Hardware Trigger/Free Run Mode
Reverse image	Horizontal Reverse, Vertical Reverse
Binning	No Support
Data interface	USB 3.0
I/O interface	6-pin Hirose connector provides power and I/O: 1 × Opto-isolated input (Line 1), 1 × Opto-isolated output (Line 2), 1 × bi-directional non-isolated I/O (Line 3)
Power supply	9 VDC to 24 VDC, supports USB3.0 power supply
Power consumption	2.26 W@5 VDC
Lens mount	C-Mount
Dimension	29 mm×29 mm×29 mm
Weight	≈ 75 g
Temperature	Working temperature: 0 °C to 50 °C, Storage temperature: 0 °C to 80 °C
Operating system	Windows 7/10/11 32/64bits, Linux 64bits, MacOS 64bits
Compatibility	USB3 Vision, GenICam
Certification	CE, RoHS, FCC, UL

Spectral Response



Dimension (mm)



I/O Interface Description



PIN	Signal	Description
1	Power	Power supply
2	Line1	Opto-isolated input
3	Line3	GPIO (I/O can be configured for non-isolated software)
4	Line2	Opto-isolated output
5	ISO_GND	Opto-isolated signal ground
6	GND	Power ground and GPIO signal ground (GND)

VISCON

Viscon Technology Co., Ltd.
54/88 Khlongsee, Khlong Luang District, Pathum Thani 12120 Thailand
Tel : 02-0009297
MB : 0809293068
E-mail : sale@viscontechnology.com

viscontechnology.com